

ECO-TRAP (POWDER)

GREASE TRAP TREATMENT

SPECIFICATIONS

Description	Free Flowing Powder
Packaging	28g, 56g, 250g, or Bulk
Stability	Up to 24 months
pH	Neutral
Nutrient Content	Biological nutrients and stimulants Bacteria
Count	5.0×10^8 cfu/g
Storage and Handling	DO NOT FREEZE! Store in a cool dry location. Do not inhale mists. Avoid excessive skin contact. See MSDS.



APPLICATION INSTRUCTIONS

Grease Trap Size	Initial Dosage	Maintenance
From 50 to 250 gallons	500 ml	350 to 500 ml per day
From 250 to 500 gallons	1L	500 to 650 ml per day

Place ECO TRAP P directly to grease trap. The water soluble pouch may be direct inserted into the grease trap, or previously dissolved in water following by applying the solution to the grease trap. ECO-TRAP is more effective when it is applied at the end of the daily activities of the institution. The bacteria in ECO-TRAP will therefore have more time to biodegrade the oils, grease, and other organic materials that accumulate in the trap.

To obtain optimal performance, it is recommended to clean out the grease trap before the initial dosage of ECO-TRAP. Results will be obtained within four to eight weeks of the initial dosage.

For a trap of more than 500 gallons, it is recommended to consult your Bionetix representative.

The information presented in this Product Sheet is believed to be reliable. This information is provided as representative only and there are no warranties, expressed or implied, regarding its performance. Since neither distributor nor manufacturer has any control over handling, storage, use and application conditions, they are not responsible for any claims, liabilities, damages, costs or expenses of any kind arising out of or in any way connected with the handling, storage or use of the product described.

CONTAINS SPECIALTY PENETRANTS AND SURFACTANTS THAT LOOSEN AND LIQUEFY HEAVY GREASE DEPOSITS, THEREBY AIDING THEIR DEGRADATION.

ECO-TRAP POWDER ADVANTAGES

- Reduces oil and fat accumulation;
- Prevents emergency blockages;
- Reduces scum build-ups;
- Improves pipe drainage;
- Reduces BOD;
- Reduces bad odors.