

ECO-TRAP (BLOC)

GREASE TRAP TREATMENT

SPECIFICATIONS

Description	Pink solid
Packaging	Box: 4x2lb blocks; 2x5lb blocks. Each block is packaged in a mesh application bag.
Stability	Up to 24 months
pH	Neutral
Bulk Density	Solid
Nutrient Content	Biological nutrients and stimulants
Bacteria Count	3 billion/gram
Storage and Handling	DO NOT FREEZE! Store in a cool dry location. Do not inhale dusts. Avoid excessive skin contact. See MSDS.

APPLICATION INSTRUCTIONS

Add the ECO-TRAP BLOC directly to the grease trap.

1. When locating the Blocs in the grease trap, DO NOT place Blocs directly into the flow of incoming sewage. The turbulence and "washing effect" will greatly reduce the longevity of this product. Ideally, the Blocs should be placed in a less turbulent area of the grease trap, but not in a dead spot.
2. The Blocs should be suspended in the grease trap so that they are



always submerged in water, even at the lowest water level. This will assure maximum contact time with the organics, providing superior results.

3. If a grease shelf is present during placement of the Blocs, it is recommended to raise the high level flow so that the bacteria can attack the grease shelf from the top, bottom, and sides.
4. Results should be obtained in four to eight weeks from the time of application. If grease shelves are

present at the time of application, a longer period of time may be required to obtain results.

Flow Rate	Dosage
50 - 500 gallons	2lb/ month
500 - 1000+ gallons	5lb/ month

For a flow rate of more than 500 gallons it is recommended to consult your BIONETIX representative.

The information presented in this Product Sheet is believed to be reliable. This information is provided as representative only and there are no warranties, expressed or implied, regarding its performance. Since neither distributor nor manufacturer has any control over handling, storage, use and application conditions, they are not responsible for any claims, liabilities, damages, costs or expenses of any kind arising out of or in any way connected with the handling, storage or use of the product described.

CONTAINS SPECIALTY PENETRANTS AND SURFACTANTS THAT LOOSEN AND LIQUEFY HEAVY GREASE DEPOSITS, THEREBY AIDING THEIR DEGRADATION.

ECO-TRAP BLOC ADVANTAGES

- Keeps floats clean;
- Reduces grease build-up;
- Prevents emergency blockages;
- Saves on line jetting;
- Lowers grease disposal costs;
- Reduces odors.