

ECO-DRAIN™ P

DRAIN MAINTAINER

PRODUCT DESCRIPTION

ECO-DRAIN™ P is a probiotic drain cleaner formulated with beneficial bacteria, enzymes, nutrients, and cleaning agents. It is capable of degrading a wide range of animal and vegetable oils and greases under aerobic, facultative, and anaerobic conditions. When applied on a regular basis, ECO-DRAIN™ P reduces the accumulation of grease in sumps, drains, and traps, thus allowing other solids to flow freely through the system. It is an excellent alternative to corrosive chemicals for gentle, efficient drain maintenance that does not harm pipes or the environment.

PACKAGING AND STORAGE

Available in water-soluble pouches (400 x 28 g per plastic pail).

Store in a cool, dry location. Packaging must be kept intact, dry, and away from sunlight. Please follow the recommendations and use the product before the best before date. Contact Bionetix® with questions. Avoid inhalation and eye contact. Avoid excessive skin contact.



FEATURES AND BENEFITS

- Keeps floats clean
- Reduces grease buildup headaches
- Prevents emergency blockages
- Saves on line jetting
- Lowers grease disposal costs
- Reduces odors

TYPICAL APPLICATIONS

ECO-DRAIN™ P is specially formulated and packaged for direct addition to drains and grease traps in

- Restaurants
- Commercial buildings

SPECIFICATIONS

Description	Aqua blue free-flowing granular powder
Fragrance	Cherry
Stability	Max. loss of 1 log/yr
pH (1% Solution)	6.0-8.5
Bacteria Count	3 billion CFU/g

APPLICATION INSTRUCTIONS

The application of ECO-DRAIN™ P should be done in a way that allows for maximum retention time in the drainage system. ECO-DRAIN™ P is supplied in water-soluble packaging for direct addition to the sewer system.

Kitchen Drains	1 pouch per day
Laundry Drains	1 pouch per day
Grease Traps	1 pouch per day

ECO-DRAIN™ P

1. Use ECO-DRAIN™ P every night. The use of ECO-DRAIN™ P should be the last step in the nightly closing routine. Before starting an ECO-DRAIN™ P regimen, it is best to have the drain lines rodded and the grease traps cleaned.
2. Stir one pouch of ECO-DRAIN™ P into 5-10 L (approximately 2 gallons) of lukewarm water (~27-32 °C [80-90 °F]). After a few minutes, most of the brown particles will settle to the bottom of the bucket, leaving the active ingredients suspended in the water. Please note that the particles will not dissolve when stirred.
3. Pour one medium-sized cup of ECO-DRAIN™ P solution down each beverage tower drain.
4. Pour one medium-sized cup of ECO-DRAIN™ P down all floor drains.
5. Important: Pour the remaining solution of ECO-DRAIN™ P down the back sinks. For this procedure, the majority of the liquid is required for maximum effectiveness on grease traps. Any remaining particles can be safely rinsed down the back sink drain with lukewarm water (~27-32 °C [80-90 °F]).
6. Discard used cup. Wash hands after using ECO-DRAIN™ P. If a night is missed, use two packets the next day. Do not use hot water (over 54 °C [130 °F]).

For further information on application, contact your Bio-netix® technical representative.

The information presented in this product sheet is believed to be reliable. This information is provided as representative only and there are no warranties, expressed or implied, regarding its performance. Since neither distributor nor manufacturer has any control over handling, storage, use, or application conditions, they are not responsible for any claims, liabilities, damages, costs, or expenses of any kind arising out of or in any way connected with the handling, storage, or use of the product described. ISSUED DATE: 04/24/24. SUPERCEDES: 08/27/08.



We Work For Nature

Bionetix® International Corporation, Inc.
21 040 rue Daoust, Ste-Anne-de-Bellevue, Quebec, Canada H9X 4C7
T. 514.457.2914
F. 514.457.3589
www.bionetix-international.com

